

AKATEK

by
KIVANÇ
Group



BASIC RANGE OF FLAME RESISTANT YARNS

Code	Composition	Single Ne	2 Ply Ne	Processing
410FB	93% Meta-Aramid, 5% Para-Aramid, 2% Antistatic	20/1 – 60/1	20/2 – 60/2	Weaving
410FR	75% Meta-Aramid, 23% Para-Aramid, 2% Antistatic	20/1 – 60/1	20/2 – 60/2	Weaving
410Z01	50% Meta-Aramid, 49% Viscose FR, 1% Antistatic	20/1 – 60/1	20/2 – 60/2	Weaving
410PV	79% Viscose FR, 20% Para-Aramid, 1% Antistatic	20/1 – 60/1	20/2 – 60/2	Weaving
410BG	55% Viscose FR, 44% Meta-Aramid, 1% Antistatic	20/1 – 60/1	20/2 – 60/2	Weaving
410LA	50% Viscose FR, 45% Meta-Aramid, 5% Para-Aramid	20/1 – 60/1	20/2 – 60/2	Weaving
415FB	93% Meta-Aramid, 5% Para-Aramid, 2% Antistatic	20/1 – 60/1	20/2 – 60/2	Knitting
415PV	79% Viscose FR, 20% Para-Aramid, 1% Antistatic	20/1 – 60/1	20/2 – 60/2	Knitting
415BG	55% Viscose FR, 44% Meta-Aramid, 1% Antistatic	20/1 – 60/1	20/2 – 60/2	Knitting

Special blends are available upon request.

Fibers We Use

- Meta-Aramid dope dyed
- Meta Aramid ecru
- Para-Aramid ecru
- Para-Aramid black
- Viscose FR ecru
- Viscose FR dope dyed
- Antistatic black
- Antistatic white

Head Office

İkitelli OSB Aykosan Sanayi Sitesi 2.Kısım 5.Ada C Blok 34490
Başakşehir / İSTANBUL / TURKEY
Tel : +90 (212) 407 04 13 Pbx
Fax: +90 (212) 671 99 26

Antalya Factory

Organize Sanayi Bölgesi
1.Kısım 1.Cadde No:23 07190
Döşemealtı / ANTALYA / TURKEY