








DUO-FACE (woven)

TECHNICAL DATA

COMPOSITION	34% Modacrylic, 34% Viscose FR, 25% Para-Aramid, 5% PA 6.6, 2% Antistatic
ARTICLE	447 - Duo-Face W 260
WEIGHT (g/m ²)	260 (±5%)
WIDTH (cm)	160 (±2)
CONSTRUCTION	Double Face
TENSILE STRENGTH EN ISO 13934-1	Warp > 900 N Weft > 650 N
TEAR STRENGTH EN ISO 13937-2	Warp > 30 N Weft > 30 N

Natural Finish, Water Repellant Finish or Wicking Finish Available

PROTECTION LEVEL

 HEAT AND FLAME PROTECTION EN ISO 11612	A1, A2, B1, C1, F1**
 ELECTROSTATIC PROTECTION EN 1149-3 & EN 1149-5	PASS**
 ELECTRIC ARC PROTECTION (BOX TEST) EN 61482-2	APC 1 (4kA)**
 ELECTRIC ARC PROTECTION (OPEN ARC) EN 61482-2	ATPV 10 cal/cm ² **
 WELDING PROTECTION EN ISO 11611	Class 1**
 HIGH VISIBILITY COLOR (YELLOW) EN ISO 20471	PASS
 LIQUID CHEMICALS EN 13034	PASS

* With Water Repellant Finish Only

** Tested After 50 Industrial Washes

CLEANING INSTRUCTIONS



Colours

High Visible

Dark Blue



AKATEK