





FIRE-RESIST (woven)

TECHNICAL DATA

COMPOSITION	75% Meta-Aramid, 23% Para-Aramid, 2% Antistatic	
ARTICLE	386 - Fire-Resist W 195	392 - Fire-Resist W 195 RS
WEIGHT (g/m ²)	195 (±5%)	195 (±5%)
WIDTH (cm)	160 (±2)	160 (±2)
CONSTRUCTION	2/1 Twill	2/1 Twill Ripstop
TENSILE STRENGTH EN ISO 13934-1	Warp > 1100 N Weft > 900 N	Warp > 1100 N Weft > 900 N
TEAR STRENGTH EN ISO 13937-2	Warp > 45 N Weft > 45 N	Warp > 45 N Weft > 45 N
ABRASION RESISTANCE EN ISO 12947-2 (12kPa)	> 100000 cycle	> 100000 cycle

Natural Finish, Water Repellant Finish or Wicking Finish Available

PROTECTION LEVEL

 HEAT AND FLAME PROTECTION ISO 11612	A1, A2, B1, C1, F1**	A1, A2, B1, C1, F1**
 ELECTROSTATIC PROTECTION EN 1149-3 & EN 1149-5	PASS**	PASS**
 FIREFIGHTING PROTECTION EN 469	PASS**	PASS**
 WILDLAND FIREFIGHTING PROTECTION EN 15384	PASS**	PASS**
TECHNICAL RESCUE PROTECTION EN 16689	N/A	N/A

* With Water Repellant Finish Only

** Tested After 50 Industrial Washes

CLEANING INSTRUCTIONS



Colours



AKATEK