







# MACO-S (woven)

## TECHNICAL DATA

COMPOSITION	60% Modacrylic, 38% Cotton, 2% Antistatic with Elastane
ARTICLE	479 - Maco-S W 300 Stretch
WEIGHT (g/m <sup>2</sup> )	300 (±5%)
WIDTH (cm)	135 (±2)
CONSTRUCTION	2/1 Twill
TENSILE STRENGTH EN ISO 13934-1	Warp > 800 N Weft > 600 N
TEAR STRENGTH EN ISO 13937-2	Warp > 25 N Weft > 25 N
ABRASION RESISTANCE EN ISO 12947-2 (12kPa)	>20000 cycle

Natural Finish, Water Repellant Finish or Wicking Finish Available

## PROTECTION LEVEL

 HEAT AND FLAME PROTECTION ISO 11612	A1, B1, C1, F1
 ELECTROSTATIC PROTECTION EN 1149-3 & EN 1149-5	PASS
 ELECTRIC ARC PROTECTION (BOX TEST) EN 61482-2	N/A
 ELECTRIC ARC PROTECTION (OPEN ARC) EN 61482-2	N/A
 WELDING PROTECTION EN ISO 11611	N/A
 LIQUID CHEMICALS EN 13034	N/A

\* With Water Repellant Finish Only

## CLEANING INSTRUCTIONS



## Colours

Dark Blue

Royal Blue

Red

Black

Orange

Dark Grey

Hi-Vis Yellow



# AKATEK