




# MACO-S (knitted)

## TECHNICAL DATA

COMPOSITION	60% Modacrylic, 38% Cotton, 2% Antistatic		
ARTICLE	352 - Maco-S K 220 Single Jersey	441 - Maco-S K 220 Ribana	442 - Maco-S K 250 Interlock
WEIGHT (g/m <sup>2</sup> )	220 (±5%)	220 (±5%)	250 (±5%)
WIDTH (cm)	200 (±5)	190 (±5)	165 (±5)
CONSTRUCTION	Single Jersey	Ribana	Interlock
BURSTING RESISTANCE EN ISO 13938-1	200 kPa	200 kPa	200 kPa

## PROTECTION LEVEL

 HEAT AND FLAME PROTECTION ISO 11612	A1, B1, C1, F1	A1, B1, C1, F1	A1, B1, C1, F1
 ELECTROSTATIC PROTECTION EN 1149-3 & EN 1149-5	PASS	PASS	PASS
 ELECTRIC ARC PROTECTION (BOX TEST) EN 61482-2	APC 1 (4kA)	APC 1 (4kA)	APC 1 (4kA)
 ELECTRIC ARC PROTECTION (OPEN ARC) EN 61482-2	ATPV 5,5 cal/cm <sup>2</sup>	N/A	N/A
 LIQUID CHEMICALS EN 13034	N/A	N/A	N/A

\* With Water Repellant Finish Only

## CLEANING INSTRUCTIONS



## Colours

Dark Blue

Royal Blue

Red

Orange

Dark Grey

Black

Hi-Vis Yellow



# AKATEK