







MAPA (woven)

TECHNICAL DATA

COMPOSITION	54% Modacrylic, 32% Meta-Aramid, 12% PA 6.6, 2% Antistatic
ARTICLE	522 - Mapa W 250
WEIGHT (g/m ²)	250 (±5%)
WIDTH (cm)	160 (±2)
CONSTRUCTION	2/1 Twill
TENSILE STRENGTH EN ISO 13934-1	Warp > 900 N Weft > 700 N
TEAR STRENGTH EN ISO 13937-2	Warp > 30 N Weft > 30 N
ABRASION RESISTANCE EN ISO 12947-2 (12kPa)	> 100000 cycle

Natural Finish, Water Repellant Finish or Wicking Finish Available

PROTECTION LEVEL

 HEAT AND FLAME PROTECTION ISO 11612	A1, A2, B1, C1, F1
 ELECTROSTATIC PROTECTION EN 1149-3 & EN 1149-5	PASS
 ELECTRIC ARC PROTECTION (BOX TEST) EN 61482-2	N/A
 ELECTRIC ARC PROTECTION (OPEN ARC) EN 61482-2	N/A
 WELDING PROTECTION EN ISO 11611	N/A
 LIQUID CHEMICALS EN 13034	N/A

CLEANING INSTRUCTIONS



Colours

Dark Blue

Royal Blue

Red

Orange

Black

Dark Grey



AKATEK