






POSEIDON (woven)

TECHNICAL DATA

COMPOSITION	79% Para-Aramid, 20% Meta-Aramid, 1% Antistatic
ARTICLE	444 - Poseidon W 200
WEIGHT (g/m ²)	200 (±5%)
WIDTH (cm)	160 (±2)
CONSTRUCTION	Special Twill
TENSILE STRENGTH EN ISO 13934-1	Warp > 800 N Weft > 700 N
TEAR STRENGTH EN ISO 13937-2	Warp > 60 N Weft > 70 N
ABRASION RESISTANCE EN ISO 12947-2 (12kPa)	> 25000 cycle

Natural Finish, Water Repellant Finish or Wicking Finish Available

PROTECTION LEVEL

 HEAT AND FLAME PROTECTION EN ISO 11612	A1, A2, B1, C1, F1**
 ELECTROSTATIC PROTECTION EN 1149-3 & EN 1149-5	PASS**
 FIREFIGHTING PROTECTION EN 469	PASS**
 WILDLAND FIREFIGHTING PROTECTION EN 15384	PASS**
 LIQUID CHEMICALS EN 13034	N/A

* With Water Repellant Finish Only

** Tested After 50 Industrial Washes

CLEANING INSTRUCTIONS



Colours

Dark Blue

Red

Gold



AKATEK