

PROTEGO (woven)

TECHNICAL DATA

COMPOSITION 50% Viscose FR, 35% Meta-Aramid, 9% PA 6.6, 5% Para-Aramid, 1% Antistatic

ARTICLE 524 - Protego W 220 RS

WEIGHT (g/m²) 220 (±5%)

WIDTH (cm) 160 (±2)

CONSTRUCTION 2/1 Twill Ripstop


TENSILE STRENGTH
EN ISO 13934-1 Warp > 750 N
Weft > 600 N


TEAR STRENGTH
EN ISO 13937-2 Warp > 45 N
Weft > 45 N

ABRASION RESISTANCE
EN ISO 12947-2 (12kPa) > 90000 cycle

Natural Finish, Water Repellant Finish or Wicking Finish Available

PROTECTION LEVEL

 **HEAT AND FLAME PROTECTION**
ISO 11612 A1, A2, B1, C1, F1

 **ELECTROSTATIC PROTECTION**
EN 1149-3 & EN 1149-5 PASS

 **FIREFIGHTING PROTECTION**
EN 469 N/A

 **WILDLAND FIREFIGHTING PROTECTION**
EN 15384 N/A

 **LIQUID CHEMICALS PROTECTION**
EN 13034 N/A

* With Water Repellant Finish Only

** Tested after 50 domestic washes

CLEANING INSTRUCTIONS



Colours

Dark Blue



AKATEK